SHERWIN
INCORPORATED
5530 Borwick Avenue • South Gate, CA 90280 • (562) 861-6324 FAX (562) 923-8370
www.sherwininc.com • email: sherwin@sherwininc.com

March 5, 2020

CERTIFICATION

We hereby certify that samples of the material identified below by batch number, have been analyzed in accordance with test methods that meet and/or exceed the detection limits for fluoride, chloride, and sulfur per ASME Boiler and Pressure Vessel Code, Section V, Article 6, paragraph T-641, 1998 - 2019 Editions and addenda, with the following results:

		FLUORIDE ASTM E165 ANNEX A4	CHLORIDE ASTM E165 ANNEX A4	SULFUR ASTM E165 ANNEX A4
DUBL-CHEK	**FGP-21**	**<0.0001%BW**	**<0.0001%BW**	**<0.0001%BW**
BATCH NO.	**027-BS22**			

We further certify that this material meets or exceeds the requirements of AMS 2644G, MIL-I-25135, Revision E and ASTM E1417.

Copies of the certification and laboratory reports are on file in our office for your inspection.

SHERWIN INCORPORATED

Cesar Quintanilla
Q.C. Laboratory

DUBL-CHEK PENETRANT PROCESS

SHERWIN EAST: 1615 Distribution Drive • Burlington, KY 41005 • (859) 525-6881 FAX (859) 525-6887

SHERWIN INCORPORATED
5530 Borwick Avenue • South Gate, CA 90280 • (562) 861-6324 FAX (562) 923-8370
www.sherwininc.com • email: sherwin@sherwininc.com

CERTIFICATE OF CONFORMANCE

Date: March 5, 2020

Product: FGP-21

Batch No.: 027-BS22

Type: I Methods: A and C

It is hereby certified that this material has been manufactured in accordance with, and conforms to, AMS 2644. Results of the required quality conformance tests, as stipulated by paragraph 4.3.2, are listed below.

Test Method Paragraph	Test Description	Results
3.3.3	Flash point i.a.w. ASTM D93	>200°F
3.3.4	Viscosity i.a.w. ASTM D445 at 100 ± 1°F	15.26 cSts
3.3.8.3.2	Fluorescent brightness i.a.w. ASTM E1135 (Type I only)	80.4%
3.3.8.5	Water tolerance (Method A only)	Infinite
3.3.8.6	Removability	Conforms
3.3.8.7	Water Content	50.73%
---	Fluoride content i.a.w. ASTM E165, Annex 4	<0.0001%BW
---	Chloride content i.a.w. ASTM E165, Annex 4	<0.0001%BW
---	Sulfur content i.a.w. ASTM E165, Annex 4	<0.0001%BW

It is further certified that this material is listed or approved for listing on QPL-AMS-2644. It also meets the requirements of MIL-I-25135E, ASTM E1417, and MIL-STD-6866.

.

SHERWIN INCORPORATED

Cesar Quintanilla
Q.C. Laboratory

DUBL-CHEK PENETRANT PROCESS